(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/019682 A1

(51) International Patent Classification[7]: F16F 9/53

(21) International Application Number: PCT/GB2004/003595

(22) International Filing Date: 20 August 2004 (20.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0319552.6 20 August 2003 (20.08.2003) GB

(71) Applicant (*for all designated States except US*): REACTEC LTD [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): BUCKINGHAM, Mark-Paul [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB). DICKSON, Stephen [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB). KEEPAX, Charles [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB). MCKEOWN, John, Paul [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB). WATSON, Peter [GB/GB]; Adaptive House, Quarryside Court, Livingston EH54 6AX (GB).

(74) Agent: KENNEDYS PATENT AGENCY LIMITED; Floor 4, Queens House, 29 St Vincent Place, Glasgow G1 2DT (GB).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: VIBRATION CONTROL SYSTEM



(57) Abstract: A variable damper with a low off-state, having an outer member (12) including a magnetic sleeve and an inner shaft (14), between which is supported an electromagnet (20). Magnetorheological fluid is inserted between the members and a flow path (25) is established over a control region between the electromagnet and the sleeve. Various embodiments of the damper are presented with the electromagnet supported on the outer member and on the shaft. A vibration control system incorporating a magnetorheological fluid variable damper is presented wherein the system provides a relative figure of merit for vibration control of at least 0.83. Devices incorporating the damper in a vibration control system are presented for snow boards, clubs, drills, engines, pumps, generators and vehicles.

WO 2005/019682 A1